1191/1190FP In-Out Heads




The 1191/1190FP 1" In-Out Heads are designed for downflow filter applications or upflow pH neutralization.

Molded out of a rugged thermoplastic resin, the 1191 Head features a ¼" FPT air vent port which can be drilled out to accept an air relief valve. The 1" Head is fully ported to provide maximum flow rates. The 1191 incorporates a standard 2½" tank connection and features parallel inlet and outlet ports to easily adapt to standard plumbing connections or Clack's all-plastic, fourway bypass valve. A full line of fitting plumbing connection kits are available.

The 1190FP Head has a removable fill port cap to allow easy access to the media bed. The 1190FP includes a removable upper distributor basket providing access to the top of the riser pipe, allowing water to be drained from the tank when replacing media. The 1190FP includes a utility wrench to be used with the removable cap. A full line of top and bottom distributors is available.





ORDER NO.	DESCRIPTION	QTY/ CARTON
D1400	1191 In-Out Head	24
D1220-01	1190FP In-Out Head w/ Fill Port (includes wrench)	12

1 of 2 3/26/2013 3:23 PM

1191/1190FP Accessories

Typical Installations:



1191 In-Out Head shown with optional V3006 Bypass Assembly and V3007-01 ¾" x 1" PVC Solvent Elbow Assembly

ORDER NO.	DESCRIPTION	QTY/ CARTON
V3006	Bypass Assembly	24
V3007	1" PVC Male NPT Elbow Assembly	24 sets
V3007-01	3/4" x 1" PVC Solvent Elbow Assembly	24 sets
V3007-02	1" Brass Sweat Assembly	24 sets
V3007-03	3/4" Brass Sweat Assembly	24 sets
V3007-04	1" Plastic Male NPT Assembly	24 sets
V3007-05	1.25" Plastic Male NPT Assembly	24 sets
V3007-06	1" Plastic Male BSPT Assembly	24 sets
V3007-07	1.25" & 1.5" PVC Solvent Assembly	24 sets
V3007-08	1.25" Plastic Male BSPT Assembly	24 sets
V3007-09	1.25" & 1.5" Brass Sweat Assembly	24 sets
V3007-12	3/4" SharkBite* Assembly	24 sets
V3007-13	1" SharkBite® Assembly	24 sets
V3007-14	3/4" Plastic Male BSPT Assembly	24 sets
V3191-01	Vertical 90° Adapter Kit	24 sets
V3193-02	Wrench	Bulk



Note: On upflow service the bypass will give two-way function capabilities (service and bypass). The red bypass handles also need to be reversed to indicate proper service flow direction.

Distributed by: Aqua Purification Systems, Inc. - USA - Fax: 408-225-7974

E-mail: sales@aquapurification.com - www.aquapurification.com - www.birmfilter.com

2 of 2 3/26/2013 3:23 PM