



QuickSeam™ Conduit Flashing

Firestone Item Number:
W563581070: Universal

DESCRIPTION:

Firestone QuickSeam Conduit Flashing is specifically designed to be used for flashing of rigid round penetrations and conduit.

METHOD OF APPLICATION:

Penetration must be clean of prior flashing and foreign materials. Cut along the top edge of the ring on the QuickSeam Conduit Flashing corresponding to the size of the pipe or conduit you are flashing.

Clean the approved Firestone membrane using QuickPrime™ Plus and a QuickScrubber™ or QuickScrubber Plus™ pad and handle to remove all dusting agent, dirt and other contaminants that will affect the finished bond. Allow to dry according to the touch-push test. Remove the release paper. Install the pipe flashing and roll the flange with a silicone hand roller. Install the clamping ring and Lap Sealant per Firestone Specialty Products specifications and details.

SHELF LIFE:

1. Shelf life of one (1) year can be expected if stored in original unopened container at temperatures between 15.6 - 26.7° C (60 - 80° F).
2. Shelf life will be shortened if exposed to elevated temperatures.
3. Rotate stock to insure stored material will not go beyond the shelf life of one (1) year.

STORAGE:

1. Store in original unopened containers at temperatures between 15.6 - 26.7° C (60 - 80° F) until ready for use.
2. When exposed to lower temperatures, restore to room temperature prior to use.

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.



PRODUCT DATA

<u>Property</u>	<u>Minimum Performance</u>
<u>QuickSeam Tape</u>	
Base:	Rubber Polymer
Color:	Black
Solvents:	None
Solids:	100%
Cured State:	Cured
Thickness:	0.762 mm +/- 0.13 mm (0.030" +/- 0.005")
<u>Molded Pipe Flashing</u>	
Base:	Molded EPDM
Color:	Black
Sizes:	Universal: Fits 12.7 mm - 64 mm (0.5" to 2.5") O.D.
Clamp:	Stainless Steel - clamps are included
Pipe Flange:	229 mm (9.0") O.D.
Thickness:	1.4 mm - 1.9 mm (0.055" - 0.075")

Fits the Pipe or Conduit Outside Diameters listed below:

<u>SI</u>	<u>Eng</u>	<u>SI</u>	<u>Eng</u>
12.70 mm	0.50"	45.00 mm	1.75"
19.00 mm	0.75"	51.00 mm	2.00"
25.40 mm	1.00"	57.15 mm	2.25"
32.00 mm	1.25"	64.00 mm	2.50"
37.00 mm	1.50"		

STORAGE (Con't):

3. Keep the material out of direct sunlight until ready for application.

PACKAGING:

10 QuickSeam Conduit Flashing are packaged per carton and 96 cartons per pallet.

PRECAUTIONARY DATA:

1. Review Material Safety Data Sheet (MSDS) prior to use.
2. Do not install over uneven substrates.

LEED INFORMATION:

Post Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: Bensenville, IL

Firestone Specialty Products
 250 West 96th Street, Indianapolis, Indiana 46260
 Specialty Products (800) 428-4442
 Internet Address: <http://www.firestonesp.com>