



Termination Bar

Firestone Item Number:
W56RAC3061: 3.05 m (10.0') Long

DESCRIPTION:

Firestone Termination Bar is intended for attaching and sealing approved Firestone membrane terminations as indicated in the current Firestone Specialty Products specifications and details.

METHOD OF APPLICATION:

Install Firestone Water Block Seal behind top of flashing. Anchor bar through pre-punched holes at a rate to maintain a seal (max. 304.8 mm (12.0") o.c.). Remove excess membrane above bottom of lap sealant reservoir channel. Install Firestone Lap Sealant into reservoir channel to seal the upper edge of the membrane where appropriate. Consult Firestone Specialty Products specifications and details for specifics.

STORAGE:

Store in original unopened container protected from the weather until ready for use.

PACKAGING:

3.05 m (10.0') pieces are packaged 50 per cardboard tube and 52 tubes per pallet.



PRODUCT DATA

Property	Minimum Performance
Material:	3003-H14, 3105-H14 or 6063-T5, or T6 Aluminum
Length:	3.05 m (10.0') Long
Height:	27.4 mm (1.08")
Thickness:	2.7 mm (0.106")
Holes:	Slotted, 7.1 x 9.9 mm (0.28 x 0.39") 30 at 99.8 mm (3.93") o.c.

PRECAUTIONARY DATA:

1. Do not use as a batten strip.
2. Where field cutting is necessary, remove any burrs from bar.
3. Clean up shavings, etc. that may occur from field cutting.
4. Install flat side of bar towards flashing so a "lip" forms a reservoir for Lap Sealant.
5. Keep each 3.05 m (10.0') length of Termination Bar separated from adjoining bar by 6.3 mm (0.25").
6. Termination bars must be installed directly to the wall surface, not to existing sheet metal, flashings, etc.
7. Install termination bar on hard, smooth surfaces only.
8. Do not install on substrates where seal is lost at mortar joints, etc.
9. Install termination bar vertically where base flashing(s) end.
10. Do not install termination bar to wood or other porous surfaces.

LEED INFORMATION:

Post Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 67%
 Manufacturing Locations: Bryan, OH
 Cleveland, OH

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice design, Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any project on which its products may be applied. If questions arise as to the soundness of a project, or its ability to support a planned installation properly, the Owner should obtain opinions of competent design engineers before proceeding. Firestone accepts no liability for any failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.