

EASY-GRIP PUSH FIT FITTINGS

Boshart EASY-GRIP Push Fit Fittings and valves are available in sizes from 1/2" to 1" designed for connecting fittings and valves to Copper, CPVC and PEX Pipe and are ideal for use on plumbing, water heaters and hydronic heating systems. They are approved for use for both underground and behind walls with/without access panels. Due to their unique design utilizing high quality EPDM O-ring and #304 Stainless Steel gripper ring no soldering, crimping, or solvent welding necessary. This makes them ideal for wet repairs where a system is hard to drain making soldering difficult with no drying time required.

SIMPLY PUSH, CONNECT AND GO!

Product Features

- EPDM O-ring and #304 Stainless Steel gripper ring eliminates the need for soldering, crimping or solvent welding.
- Excellent for wet, hazardous and dry repairs of existing plumbing and as a safe method for repairing piping in hard to access situations where open flame could be a fire hazard for soldering
- Plastic assembly clip is used as a special disconnect tool to release the tube, making for an easy disconnection if needed.

Max. Pressure: 200 psi (1378 kPa)

Max. Temperature: 200°F (93°C) - Water

Tube Insert

Polysulfone stiffener inserts included with every fitting at no extra cost.



IAPMO Certification

Products comply with the applicable section of the latest edition of the Uniform Plumbing Code® and the International Plumbing Code®. Models listed to the National Plumbing Code of Canada and Relevant Canadian Standard(s) shall bear the cUPC mark of conformity.

Ball Valves – IAPMO File No. 5598

- Manufactured in compliance with IGC 157-2010.

Push Fit Fittings – File No. 5550

- Push fit fittings can be utilized in underground applications and as manufactured joints without access panels. To be installed in accordance with the manufacturer's instructions and the latest edition of the Uniform Plumbing Code.
- Manufactured in compliance with ASSE 1061-2006

IAPMO Drinking Water System Components

- Health Effects File No. N-5213

Products comply with the applicable section of the International Plumbing Code®. Manufactured in compliance with NSF/ANSI 61-2008.

In compliance with:



Tested By:

