

ACCESSORIES

Cord Seal, Cable Clamp Assembly, Float Brackets, Pipe Mounting Bracket, Cable Connectors, Hub Assembly, Cable Weights, ETM w/ Piggy-Back Plug, Post Junction Box, Vertical Reed Switch, Anchor, and Chain

CORD SEAL

Provides strain relief and a liquid-tight seal.

- Seals 1-3 cables in 2" terminal adapters
- 2 PVC plugs included (for unused cable positions)
- Ground wire

SEAL: neoprene

WASHERS: stainless steel

NUT AND BOLT: stainless steel

WIRE/CABLE ACCOMMODATED: SJOW, SJTW, 18/2, 18/3, 16/2, 16/3, 14/2 and 14/3



Part Number	Description
1008517	Cord Seal

CABLE CLAMP ASSEMBLY

Provides cable anchor point and strain relief. Secures cable in vertical direction.

- For use with 18/16 gauge, 14 gauge, & 12 gauge cable
- Mounting clamp: ABS Nylon blend
- Hose clamp: highly corrosion resistant stainless steel




Part Number	Description
1008569	18 & 16 Gauge Cable Clamp Assembly
1008574	14 Gauge Cable Clamp Assembly
1008575	12 Gauge Cable Clamp Assembly

FLOAT BRACKET

Provides convenient installation of float switches.

- Six Float Bracket supports 1-6 floats
- Four Float Bracket supports 1-4 floats
- Can be directly mounted to wall or used with wall mounting device
- Provides convenient location to stow excess float cord
- Supplied with UL Recognized cord strain relief connectors




METAL COMPONENTS: all metal components are made of 300 series stainless steel

STRAIN RELIEF CONNECTORS: which accommodate 18/2, 18/3, 16/2, 16/3 SJOW and SJTW cords

Part Number	Description
1009432	4 Float Bracket With Mounting Device
1009433	4 Float Bracket Without Mounting Device
1009434	6 Float Bracket With Mounting Device
1009435	6 Float Bracket Without Mounting Device
1009436	Float Bracket Mounting Device

PIPE MOUNTING BRACKET

- Secures discharge pipe to basin wall.
- Clamps directly to 2" PVC discharge pipe.



Part Number	Description
1030359	Pipe Mounting Bracket

PRODUCTS CONTINUED ON NEXT PAGE.
SEE PRICE BOOK FOR LIST PRICES.

CABLE CONNECTORS

Provides strain relief and a liquid-tight seal.

- UL Listed and CSA Certified



ROUND CABLE SPECIFICATIONS

MATERIAL: polyimid flame-resisting, self-extinguishing plastic

ORING: neoprene plastic

HOLE REQUIREMENT: NPT threaded OR clearance holes (jam nut included)




RCC-8

NPT Hub: .5 inch (1.27cm)

Maximum Diameter: .480 inch (1.22 cm)

Minimum Diameter: .270 inch (.68 cm)

Wire/Cable (AWG) Accommodated: 18/2, 18/3, 18/4, 16/2, 16/3, 16/4, 14/2, and 14/3



RCC-12

NPT Hub: .75 inch (1.90 cm)

Maximum Diameter: .709 inch (1.80 cm)

Minimum Diameter: .545 inch (1.38 cm)

Wire/Cable (AWG) Accommodated: 14/2, 14/3, 14/4, 12/2, 12/3, 12/4, 10/2, and 10/3

RCC-16

NPT Hub: 1.0 inch (2.54 cm)

Maximum Diameter: .98 inch (2.49 cm)

Minimum Diameter: .71 inch (1.80 cm)

Wire/Cable (AWG) Accommodated: Round cable with outside diameter within range indentified above.

Part Number	Description
1002574	1/2 inch Round Cable Connector (RCC-8)
1002575	3/4 inch Round Cable Connector (RCC-12)
1009868	1 inch Round Cable Connector (RCC-16)

FLAT UF CABLE SPECIFICATIONS

MATERIAL: weather-stabilized thermo plastic

ORING: neoprene plastic

HOLE REQUIREMENT: NPT threaded OR clearance holes (jam nut included)




UFCC-8

NPT Hub: .50 inch (1.27 cm)

Maximum: .26 x .56 inch slot

Wire/Cable (AWG) Accommodated: 14/2, 12/2, 10/2



UFCC-12

NPT Hub: .75 inch (1.90 cm)

Maximum: .26 x .60 inch slot

Wire/Cable (AWG) Accommodated: 14/3, 12/3

Part Number	Description
1002576	1/2 inch Flat UF Cable Connector (UFCC-8)
1002577	3/4 inch Flat UF Cable Connector (UFCC-12)

SJE Rhombus

PO Box 1708, Detroit Lakes, MN 56502

1-888-DIAL-SJE • 1-218-847-1317

1-218-847-4617 Fax

email: sje@sjerhombus.com

www.sjerhombus.com 121

ACCESSORIES

Cord Seal, Cable Clamp Assembly, Float Brackets, Pipe Mounting Bracket, Cable Connectors, Hub Assembly, Cable Weights, ETM w/ Piggy-Back Plug, Post Junction Box, Vertical Reed Switch, Anchor, and Chain

HUB ASSEMBLY

Provides liquid-tight conduit attachment location.

- Available in 1, 1.5 and 2 inch sizes.
- UL Listed and CSA Certified terminal adapter



TERMINAL ADAPTER (HUB): PVC

GASKET: neoprene

LOCK NUT: metal

Part Number	Description
1009305	1 inch Hub Assembly
1008848	1.5 inch Hub Assembly
1008849	2 inch Hub Assembly

CABLE WEIGHT

Provides an accurate pivot point for suspended float switches.

- Gripper teeth on clip and weight channel securely lock float cable into place
- Cable Weight can be adjusted without the use of tools



U.S. Patent 5,306,885

HOUSING: 1 pound, 12 ounce (0.8 kgs.), 2.8 inch diameter x 3.3 inch long (7.1 cm diameter x 8.4 cm), impact resistant, non-corrosive, PVC housing for use in liquids up to 140°F (60°C).

CLIP: injection molded acetal plastic

WIRE/CABLE ACCOMMODATED: SJOW, SJTW, 18/2, 18/3, 16/2, 16/3, 14/2 and 14/3

SHIP WEIGHT: 2 lbs.

Part Number	Description
1002230	Cable Weight

CABLE WEIGHT MINI

Provides an accurate pivot point for suspended float switches.

- One piece cable weight
- Turn and Lock for easy installation.



HOUSING: 9.6 ounces (0.27 kgs.), 2.5 inch diameter x 2.5 inch long (6.35 cm diameter x 6.35 cm), impact resistant, non-corrosive, PVC housing for use in liquids up to 140°F (60°C)

WIRE/CABLE ACCOMMODATED: SJOW, SJTW, 18/2, 18/3

Part Number	Description
1030356	Cable Weight Mini

ETM WITH 120V PIGGY-BACK PLUG

Plugs into switched outlet or piggy-back switch of plugger control panel. Unit must be placed inside an enclosure.

- 120 VAC
- Screws and mounting adhesive included.



Part Number	Description
1022846	ETM w/120V piggy-back plug

POST JUNCTION BOX

- Convenient, safe location for remote wiring.
- 2 foot post with removable cap.
- Large terminal block includes touch-safe shield.
- Vent holes prevent moisture condensation.



Part Number	Description
1023992	Post Junction Box

VERTICAL REED SWITCH

- Control differential: .375 inch (1 cm)
- Maximum angle from vertical: 5°
- Electrical: 250 mAmps, 12-125 VAC, 50/60 Hz
500 mAmps, 6-12 VDC, 50/60 Hz
- Housing and Float: 1.60 inch diameter x 6.7 inch long (4.06 cm X 17.01 cm), high impact, corrosion resistant PVC for use in sewage and non-potable water up to 120°F (50°C)



Part Number	Description
1011027	10ft VRS 120V Bulk
1016561	15ft VRS 120V Bulk

ANCHOR

- 10 lb. weight
- Yellow, vinyl coated, mushroom style



Part Number	Description
1018687	10 lb. Mushroom Anchor

CHAIN

- 1/8" thickness
- 316 grade stainless steel
- Available in one foot increments



Part Number	Description
1018823	1/8 inch Chain

www.sjerhombus.com
sje@sjerhombus.com

Call or fax your order!

1-888-DIAL-SJE (1-888-342-5753) / Fax 218-847-4617