

Tank Alert® AB Alarm

- The Tank Alert® AB indoor alarm offers auto reset and battery backup features. The horn sounds when a potentially threatening liquid level occurs.
- · NEMA 1 rated for indoor use.
- Red alarm light, green power light, alarm test switch, horn silence switch.
- · UL Listed: CSA Certified.



Tank Alert® ABP Alarm

- The Tank Alert® ABP indoor alarm not only offers auto reset and battery backup, but also features pump control capabilities via a 120V receptacle to accept pump plug.
- NEMA 1 rated for indoor use.
- · Provides manual control of pump.
- Includes 2 factory-spliced switches.
- UL/cUL Listed.



Tank Alert® I Alarm

- The Tank Alert® I indoor alarm sounds when a potentially threatening liquid level occurs. Alarm (when installed on separate circuit) operates even if pump circuit fails.
- NEMA 1 rated for indoor use.
- Red alarm light, green power light, alarm test switch, horn silence switch.
- UL Listed; CSA Certified.



Tank Alert® XT Alarm

- The Tank Alert® XT indoor/outdoor alarm meets NEC standards for junction boxes. OPTION: Pre-mounted terminal block so enclosure can be used as junction box for cord splices.
- · Rain-tight outdoor enclosure.
- Automatic alarm reset, horn silence switch, alarm test switch.
- UL Listed; CSA Certified.



Tank Alert® Duo Alarm

- The Tank Alert® Duo alarm monitors two level conditions; alarm horn and beacon activate in **flashing mode** for high water alarm condition and activate in **constant on mode** for alarm 2 (filter).
- · Rain-tight outdoor enclosure.
- · Alarm 2 input for optional float.
- · CSA Certified.



Tank Alert® 4X Alarm

- The Tank Alert® 4X indoor/outdoor alarm sounds when a potentially threatening liquid level condition occurs.
- NEMA 4X enclosure.
- Automatic alarm reset, alarm test/normal/silence switch.
- Optional auxiliary alarm contacts.UL/cUL Listed.



Tank Alert® Alarm Systems



Tank Alert® liquid level alarms visually and audibly warn of threatening liquid level conditions in lift pump chambers, sump pump basins, holding tanks, sewage and other non-potable water applications.

Each alarm can serve as either a high or low level alarm, depending upon the float switch model used.

- Tank Alert® AB Alarm
- Tank Alert® ABW Alarm
- Tank Alert® ABP Alarm
- Tank Alert® I Alarm
- Tank Alert® XT Alarm
- Tank Alert® Duo Alarm
- Tank Alert® 4X Alarm

The Tank Alert[®] AB, XT and 4X alarms offer **optional auxiliary alarm contacts** for easy attachment of remove devices.



Tank Alert® ABW Wireless Alarm

- · Auto reset, Battery backup, Wireless
- Battery operated wireless transmitter that is placed in the tank up to 150 ft. away from alarm; when high water alarm switch is activated, the transmitter sends a signal to sound the alarm.
- NEMA 1 rated for indoor use.
- Red alarm light and green power on switch.
- · Alarm test switch and horn silence switch.
- · Loss of signal alarm.
- Meets FCC Requirements.