

# Mini Rack Systems

- Available with 1, 2 or 3 filter housings
- Available without filter housings
- Nominal 10 to 16 gpm flow rates at 30mj UV dose
- 3/4" porting
- Audio/visual lamp timer included on UV system
- Stainless steel interconnect plumbing



UVDynamics Mini-Rack Systems combine up to three Big Blue style filter housings and a UV disinfection system into one simple, clean looking, and integrated product line. Manufactured from rugged 10 gauge HR commercial grade steel and finished in a tough powder coat finish, the system will stay looking good as new for many years.

The Mini-Rack system uses a special variation of our standard disinfection chamber and is equipped with a bottom mounted 1/4" drain plug to facilitate winterization in seasonal applications.

UVDynamics Mini-Rack systems speed installation, are easy to service and provide lasting value.



[www.uvdynamics.com](http://www.uvdynamics.com)

UVDynamics Inc.  
315 Neptune Crescent  
London, Ontario  
Canada, N6M 1A9  
t 800.667.4629 f 519.452.1701  
email [sales@uvdynamics.com](mailto:sales@uvdynamics.com)

# PRODUCT OVERVIEW Mini Rack Systems

Select a top plate with 1, 2, or 3 filter sump mounting footprints:

Model	TP1	TP2	TP3
Height	5" ( 13cm )	9" ( 23cm )	9" ( 23cm )
Width	15" ( 38cm )	24" ( 61cm )	31.5" ( 80cm )
Depth	7" ( 18cm )	8.5" ( 21.5cm )	8.5" ( 21.5cm )
Port Size *	¾" FNPT inlet ¾" MNPT outlet	¾" FNPT inlet ¾" MNPT outlet	¾" FNPT inlet ¾" MNPT outlet



All Mini Rack Systems can be purchased with or without 10" or 20" filter sumps.

Select an ultraviolet disinfection unit:

Ultraviolet Disinfection Unit	MR240	MR320E	MR320	MR400	MR400E
16mj/cm <sup>2</sup> (NSF) Note 1	15gpm (57L) ( 3.4m <sup>3</sup> /hr )	20gpm (76L) ( 4.5m <sup>3</sup> /hr )	20gpm (76L) ( 4.5m <sup>3</sup> /hr )	25gpm (94L) ( 5.6 m <sup>3</sup> /hr )	25gpm (94L) ( 5.6 m <sup>3</sup> /hr )
30mj/cm <sup>2</sup> (Industry Standard) Note 2	8gpm (30L) ( 1.8m <sup>3</sup> /hr )	10gpm (37L) ( 2.2m <sup>3</sup> /hr )	10gpm (37L) ( 2.2m <sup>3</sup> /hr )	13gpm (45L) ( 2.9m <sup>3</sup> /hr )	13gpm (45L) ( 2.9m <sup>3</sup> /hr )
40mj/cm <sup>2</sup> (NSF/EPA)	6gpm (23L) ( 1.38m <sup>3</sup> /hr )	8gpm (30L) ( 1.8m <sup>3</sup> /hr )	8gpm (30L) ( 1.8m <sup>3</sup> /hr )	10gpm (37L) ( 2.2m <sup>3</sup> /hr )	10gpm (37L) ( 2.2m <sup>3</sup> /hr )
Chamber Length	18" ( 48cm )	18" ( 48cm )	18" ( 48cm )	22" ( 59cm )	22" ( 59cm )
Cell Diameter	3.5" ( 8.9cm )	3.5" ( 8.9cm )	3.5" ( 8.9cm )	3.5 ( 8.9cm )	3.5" ( 8.9cm )
AC Supply Voltage	120V or 240V 47-63Hz	120V or 240V 47-63Hz	120V or 240V 47-63Hz	120V or 240V 47-63Hz	120V or 240V 47-63Hz
Power (watts)	33 watts	40 watts	40 watts	44 watts	44 watts
Lamp Watts	30 watts	35 watts	35 watts	40 watts	40 watts
Max. Pressure Note 3	100psi (6.9bar)	100psi (6.9bar)	100psi (6.9bar)	100psi (6.9bar)	100psi (6.9bar)
Water Temperature	40° – 99° F ( 4° – 37° C )	40° – 99° F ( 4° – 37° C )	40° – 99° F ( 4° – 37° C )	40° – 99° F ( 4° – 37° C )	40° – 99° F ( 4° – 37° C )
Maximum Ambient Temp.	104° F ( 40° C )	104° F ( 40° C )	104° F ( 40° C )	104° F ( 40° C )	104° F ( 40° C )
Visual LAMP ON Indicator	Yes	Yes	Yes	Yes	Yes
Isolated Solenoid Output	No	No	Yes	Yes	No
UV Monitor	Not Available	Not Available	Option	Option	Not Available
Chamber Material	304 S.S.	304 S.S.	304 S.S.	304 S.S.	304 S.S.



## Model # Formula: MRxxx-TPy/BBzzz

where:

**xxx** is the ultraviolet disinfection unit

**y** is the number of sump mounting footprints

**zzz** is the size of filter sumps required

(1 denotes 10", 2 denotes 20", 0 denotes no sump)

eg. **MR320E-TP2/120** would be a mini rack system with a UVD320E disinfection unit and two filter sumps, one 10" and one 20".

Note 1 - 16mj/cm<sup>2</sup> Dose is suitable for reducing nonpathogenic nuisance organisms only. Disinfection chamber hydraulic performance may limit maximum flow rate.

Note2 - 30mj/cm<sup>2</sup> Industry standard Dose – This is the dosage produced by 2.5" diameter disinfection chambers when designed using the 1966 US Department of Health UV disinfection Policy Statement.

Note 3 – Pressure rating is for UV disinfection system only. Total system pressure rating will be dependent on filter cartridge pressure rating.



[WWW.UVDYNAMICS.COM](http://WWW.UVDYNAMICS.COM)

UVDynamics Inc.  
315 Neptune Crescent  
London, Ontario  
Canada, N6M 1A9  
t 800.667.4629 f 519.452.1701  
email sales@uvdynamics.com