3" INGROUND 12V

5031



LANDSCAPE LIGHTING







Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

Landscape Wall Wash luminaire

FEATURES

- Tiltable and adjustable beam angle
- Integral dimmer
- IP67 rated, protected from temporary immersion under water
- Drive over up to 4500lbs
- Solid diecast brass or corrosion resistant aluminum
- Available concrete pour kit
- 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- Not suitable to use with external dimmers

SPECIFICATIONS

Input: 9 - 15VAC (Transformer is required)

Power: 2W to 12W / 2VA - 17VA **Brightness:** 70 lm to 505 lm

Beam Angle: 15° to 60°

CRI: 85

Rated Life: 55,000 hours

IEC safety Standard	Walk over	Drive over
Resistance to static load test	Yes (1125lbs)	Yes (4496lbs)
Resistance to torque and shear loads test	N/A	Yes

ORDERING NUMBER

		Color Temp		Finish	
5031	3" Inground 12V	27 30	2700K 3000K	BZ BBR	Bronze on Aluminum Bronze on Brass

5031-


Example: 5031-30BBR

3" INGROUND 12V

5031

WAC

LANDSCAPE LIGHTING



Typical Inground

Most light output goes into the air,
causing light pollution



Adjust Beam Angles

Presets at

15°, 30°, 45°, 60°



Adjustable WAC Inground
Adjust the light to where you need it



Typical Inground

Most light output goes into the air,
causing light pollution




Tilt and Aim
Up to 40° of adjustability preset at
-20°, -10°, 0°, 10°, 20°



Adjustable WAC Inground Adjust the light to where you need it







Control Brightness Adjustable from 70lm to 505lm Presets Comparable to 10W, 25W, 35W, 50W, 75W Halogen source

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 **Western Distribution Center** 1750 Archibald Avenue Ontario, CA 91760



Rock Guard

Protects the fixture face



5030-GRD-BZBronze on Aluminum

5030-GRD-BBR *Bronze on Brass*

Optics

Enhances saturation of florals and foliage



LENS-25-AMB

Green

LENS-25-RED *Red*

LENS-25-FR *Frosted*

Amber

LENS-25-GRN LENS-25-BLU

Blue

LENS-25-HCL

Honeycomb Louver Reduces glare


Concrete Pour Kit

For installation in concrete Five ½" NPT threaded holes, PC

5030-PIP-PVC

Shown with temporary dense foam cap





Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS *150W Max*

9300-TRN-SS *300W Max*

9600-TRN-SS 600W Max

