DUO CCT MINI WALL WASH 12V

33/6

5121-27/30



LANDSCAPE LIGHTING

Fixture Type:			
Catalog Numbe	er:		

Project:

Location:



Select Warm White (2700K) or Pure White light (3000K)

Continuously adjust brightness

PRODUCT DESCRIPTION

Landscape Wall Wash luminaire

FEATURES

- A uniform wide distribution wall wash from a small form factor
- Integral brightness control select color temperature option
- IP66 rated, Protected against high-pressure water jets
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- Not suitable to use with external dimmers

ORDERING NUMBER

			Color Te	emp	Finish	
5	121	Mini Wall wash 12V	27/30	2700K or 3000K	BK BZ BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass

5121-____

Example: 5121-27/30BZ

SPECIFICATIONS

Input:	9 - 15VAC (Transformer is required)
Power:	1W to 8W / 2VA - 12VA
Brightness:	80 lm to 420 lm
Beam Angle:	Asymmetrical (70° by 95°)
CRI:	85
Rated Life:	60,000 hours

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. FEB 21 2018

DUO CCT MINI WALL WASH 12V

5121-27/30

WAC

LANDSCAPE LIGHTING

Accessories					
Additional Stake	9000-ST9-BK		Bronze		Durable PC stake
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BBR		Bronze on Aluminum Bronze on Brass		Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box
Guardian Mount	9000-SP9-BZ		Stainless Steel		Heavy duty stainless steel spike to position fixture Formed from a single piece of metal
Gutter Mount Bracket	5000-GM-BZ		Stainless Steel		Stainless Steel universal mounting bracket for gutter mounting fixture
Tree Mount Junction Box	5000-TCP-BZ		Bronze on Aluminu	m	Bronze on Aluminum box with Stainless steel mounting screws. Two $\frac{1}{2}$ " NPT threaded holes
Optics	LENS-2X3-AMB LENS-2X3-GRN LENS-2X3-RED	Amber Green Red	LENS-2X3-BLU LENS-2X3-FR LENS-2X3-SPR	Blue Frosted Spread	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BZ 5000-X08-BZ 5000-X12-BZ	4 in 8 in 12 in	5000-X18-BZ 5000-X24-BZ	18 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ		Bronze		

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS 75W Max **9150-TRN-SS** 150W Max **9300-TRN-SS** *300W Max*



waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122

9600-TRN-SS

600W Max

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. FEB 21 2018